

CB TEST CERTIFICATE CERTIFICAT D'ESSAI OCProduct
ProduitName and address of the applicant
Nom et adresse du demandeurName and address of the manufacturer
Nom et adresse du fabricantName and address of the factory
Nom et adresse de l'usineNote: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la deuxième pageRatings and principal characteristics
Valeurs nominales et caractéristiques principalesTrademark (if any)
Marque de fabrique (si elle existe)Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeur
Model / Type Ref.
Ref. De typeAdditional information (if necessary may also be reported on page 2)
Les informations complémentaires (si nécessaire, peuvent être indiqués sur la deuxième pageA sample of the product was tested and found to be in conformity with
Un échantillon de ce produit a été essayé et a été considéré conforme à laAs shown in the Test Report Ref. No. which forms part of this Certificate
Comme indiqué dans le Rapport de tests numéro de référence qui constitue partie de ce CertificatThis CB Test Certificate is issued by the National Certification Body
Ce Certificat de test OC est établi par l'Organisme National de Certification

Switch mode power supply (for building-in)

EOS Power India PVT Ltd.
Unit #57, SDF II, Seepz-Sez, Andheri (East)
Mumbai 400 096
IndiaEOS Power India PVT Ltd.
Unit #57, SDF II, Seepz-Sez, Andheri (East)
Mumbai 400 096
IndiaEOS Power India PVT Ltd.
Unit #57, SDF II, Seepz-Sez, Andheri (East)
Mumbai 400 096
India Additional information on page 2

1A (Max), 100-240V~ or 100-277V~ , 47-63Hz or 120 – 390 (DC), Cl. I



CTF Stage 3

ULP40-1ZXX-YYYY-MMMM

 Additional information on page 2

IEC 62368-1:2018

403696

Additional information(if necessary)**Information complémentaire (si nécessaire)**

In model name, Z = 0-9 denoting various types of connector (0- for screw terminal; 2-Inverted Header type; 3-Header type). XX is any numeric from 0-9 representing the output voltage,(Representing the output voltage which can be any voltage in the range 5V to 58V, max current as stated in ref table). YYYY is any alpha or numeric character or blank (denotes minor output variation and /or minor SELV circuit variation); first Y as -H denotes power supply with input range of 100-277 Vac. M= Blank or any alpha, numeric or alphanumeric character denoting type of mechanical accessory. (e.g. B= Base Plate, L= L bracket, U= U channel, CK= Cover Kit)



Philip Pedersen vei 11,
NO-1366 Lysaker, Norway

Date: 10-09-2020

A handwritten signature in blue ink, appearing to read "Juan Z. Saussey".

Signature: Juan Z. Saussey
Certification Department