

Product	AC-DC switching power supply
Applicant	EOS Power India PVT Ltd. Unit #57, SDF II, Seepz-Sez, Andheri (East) Mumbai 400 096 India
Manufacturer	EOS Power India PVT Ltd. Unit #57, SDF II, Seepz-Sez, Andheri (East) Mumbai 400 096 India
Factory	EOS Power India PVT Ltd. Unit #57, SDF II, Seepz-Sez, Andheri (East) Mumbai 400 096 India
Ratings	11A, 100-240Vac, 47-63Hz; Output: 1000W max.
Trade mark	
Model / Type Ref.	VPS1000-1XXX-YYYY-R
Principal characteristics	Cl. I, X = may be any numeric from 0-9 (Representing the output voltage which can be any voltage in the range 12V to 58V, max current as stated in ref table) Y = may be any alpha, numeric or alphanumeric character or blank (denotes minor output variation and /or minor SELV circuit variations) R = Indicates units with built-in redundant diode (Optional)
A sample of the product was tested and found to be in conformity with	ITAV EN 62368-1:2014;A11
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.
Additional model(s)	(2) See page 2

Date of issue 12-02-2019



Jiyea Gim
Certification Department

Nemko AS
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com
ENTERPRISE NUMBER NO974404532

Additional model(s)

Product
Pos. No
Model / Type Ref.
Trade mark (if different from page 1)
Rating
Principal characteristics

AC-DC switching power supply
1
VPS800-1ZXX-YYYY-R

Input: 8.0A, 100-240Vac, 47-63Hz; Output: 800W max.
Cl. I, Z = may be 'S', 'T' or 0
(Representing type of top cover, S= Slotted, T= Plain and 0= no top cover)
X = may be any numeric from 0-9 (Representing the output voltage which can be any voltage in the range 12V to 58V, max current as stated in ref table)
Y = may be any alpha, numeric or alphanumeric character or blank (denotes minor output variation and /or minor SELV circuit variations)
R = Indicates units with built-in redundant diode (Optional)

Product
Pos. No
Model / Type Ref.
Trade mark (if different from page 1)
Rating
Principal characteristics

AC-DC switching power supply
2
VPS600-1ZXX-YYYY-R

6.5A, 100-240Vac, 47-63Hz; Output: 600W max.
Cl. I, Z = may be 'S', 'T' or 0
(Representing type of top cover, S= Slotted, T= Plain and 0= no top cover)
X = may be any numeric from 0-9 (Representing the output voltage which can be any voltage in the range 12V to 58V, max current as stated in ref table)
Y = may be any alpha, numeric or alphanumeric character or blank (denotes minor output variation and /or minor SELV circuit variations)
R = Indicates units with built-in redundant diode (Optional)

Date of issue 12-02-2019



Jiyea Gim
Certification Department

Nemko AS
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com
ENTERPRISE NUMBER NO974404532